


## DOWNLIGHT LIDER M 850 21W 60° WHITE | ON/OFF

Article number: N203-K0003-RF850-H5-M60-ZC02\_550-S2-###





COB Light colour 5000 [K] | CRI Led chip flux 3185 [lm] Luminous flux 2866 [lm] System power 21 [W] Luminaire Efficiency 136 [lm/W] Beam angle 60° Controller ON/OFF MacAdam 3 SDCM

## **Downlight LED**

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W

## LUMINAIRE

 Weight
 0,61 [kg]

 Protection rating IP , IK , class
 IP 20, IK 1,

 Luminaire colour
 WHITE

 Cover
 Plastic

 Operating voltage
 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska