


DOWNLIGHT LIDER M 930 27W 23° WHITE | ON/OFF

Article number: N203-K0003-RF930-H5-M23-ZC01_700-S2-###



| | |
|----------------------|------------|
| LED | COB |
| Light colour | 3000 [K] |
| CRI | 90 |
| Led chip flux | 3227 [lm] |
| Luminous flux | 2904 [lm] |
| System power | 27 [W] |
| Luminaire Efficiency | 108 [lm/W] |
| Beam angle | 23° |
| Controller | ON/OFF |
| MacAdam | 3 SDCM |

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

LUMINAIRE

| | |
|-----------------------------------|------------------|
| Weight | 0,61 [kg] |
| Protection rating IP , IK , class | IP 20, IK 1, |
| Luminaire colour | WHITE |
| Cover | Plastic |
| Operating voltage | 220-240V 50-60Hz |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl
cora@cora.pl



Street: Ignatza Hakuby 18
41-914 Bytom, Polska