

DOWNLIGHT LIDER M 930 25W 38° WHITE | ON/OFF

Article number: N203-K0003-RF930-H5-M38-ZC02_650-S2-###



Downlight LED

Light colour 3000 [K] | CRI 90 2997 [lm] Led chip flux Luminous flux 2697 [lm] System power 25 [W] Luminaire Efficiency 108 [lm/W] Beam angle 38° Controller ON/OFF MacAdam 3 SDCM

COB

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W.

LUMINAIRE

Weight	0,61 [kg]
Protection rating IP , IK , class	IP 20, IK 1,
Luminaire colour	WHITE
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska DOWNLIGHT