


DOWNLIGHT LIDER M 825 23W 38° WHITE BREAD ON/OFF

Article number: N203-K0003-VF825-H5-M38-ZC02_600-S2-###





.ED COB

Light colour 2500 [K] BREAD

CRI 8

 Led chip flux
 2808 [lm]

 Luminous flux
 2527 [lm]

 System power
 23 [W]

 Luminaire Efficiency
 110 [lm/W]

 Beam angle
 38°

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

Weight 0,61 [kg]

Protection rating IP , IK , class IP 20, IK 1,

Luminaire colour WHITE

Cover Plastic

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling istallation. Aluminium housing. Plastic cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 15°, 23°, 38° and 60°. Maximum power is 27W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on inquiry, Casambi on inquiry, DALI on inquiry, Phase-cut dimming on inquiry.



Generated: 17.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska