

## DOWNLIGHT

## DOWNLIGHT SHERIFF M 930 31W 30° GREY HI EFFICIENT ON/OFF

Article number: N204-K0001-BB930-H8-H30-ZC03\_800-S6-###



COB

90

3000 [K] HI EFFICIENT

4956 [lm]

3964 [lm]

128 [lm/W]

ON/OFF

3 SDCM

31 [W]

30°



## Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

LUMINAIRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

JMINAIRE	
Weight	1,03 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

## Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

 ${\sf RAL}$  colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl  $\bigcirc$ 

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.05.2024