

DOWNLIGHT

DOWNLIGHT SHERIFF M 940 21W 15° GREY HI EFFICIENT ON/OFF

Article number: N204-K0001-BB940-H8-H15-ZC02_550-S6-###



LED	СОВ
Light colour	4000 [K] HI EFFICIENT
CRI	90
Led chip flux	
Luminous flux	3492 [lm]
System power	2793 [lm]
Luminaire Efficiency	21 [W]
	133 [lm/W]
Beam angle	15°
Controller	
MacAdam	ON/OFF
	3 SDCM
UMINAIRE	
Weight	1,03 [kg]
Protection rating IP , IK , class	IP 20, IK 3,

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

L

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.

GREY

Glass

220-240V 50-60Hz





+48 32 388 80 00

www.cora.pl cora@cora.pl \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 15.05.2024