


## DOWNLIGHT SHERIFF M 940 34W 15° GREY HI EFFICIENT ON/OFF

Article number: N204-K0001-BB940-H8-H15-ZC03\_900-S6-###







LED	COB
Light colour	4000 [K] HI EFFICIENT
CRI	
Led chip flux	90
	5532 [lm]
Luminous flux	4425 [lm]
System power	4423 [111]
Luminaira Efficiancy	34 [W]
Luminaire Efficiency	130 [lm/W]
Beam angle	
Controller	15°
Controller	ON/OFF
MacAdam	0.0,0.
	3 SDCM

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

## LUMINAIRE

Weight 1,03 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour GREY

Cover Glass

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 22.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska