

## DOWNLIGHT

## DOWNLIGHT SHERIFF M 940 10W 45° GREY HI EFFICIENT ON/OFF

Article number: N204-K0001-BB940-H8-H45-ZC01\_250-S6-###



COB

90

4000 [K] HI EFFICIENT

1625 [lm]

1300 [lm]

130 [lm/W]

ON/OFF

3 SDCM

10 [W]

45°



## Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

LUMINAIRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

1,03 [kg]
IP 20, IK 3,
GREY
Glass
220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska

