

DOWNLIGHT

DOWNLIGHT SHERIFF M 940 14W 60° GREY HI EFFICIENT ON/OFF

Article number: N204-K0001-BB940-H8-H60-ZC01_350-S6-###



LED	СОВ
Light colour	4000 [K] HI EFFICIENT
CRI	90
Led chip flux Luminous flux System power	2260 [lm]
	1808 [lm] 14 [W]
Luminaire Efficiency Beam angle	129 [lm/W]
Controller MacAdam	60° ON/OFF
MacAdam	3 SDCM
UMINAIRE	
Weight	1,03 [kg]
Protection rating IP , IK , class	IP 20, IK 3,

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

L

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.

GREY

Glass

220-240V 50-60Hz





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 15.05.2024