


DOWNLIGHT SHERIFF M 940 21W 60° GREY HI EFFICIENT ON/OFF

Article number: N204-K0001-BB940-H8-H60-ZC02_550-S6-###







LED	COB
Light colour	4000 [K] HI EFFICIENT
CRI	90
Led chip flux	30
	3492 [lm]
Luminous flux	
Custom news	2793 [lm]
System power	21 [W]
Luminaire Efficiency	Z 1 [VV]
	133 [lm/W]
Beam angle	
0 1 1	60°
Controller	ONVOEE
MacAdam	ON/OFF
Maor wall	3 SDCM

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

LUMINAIRE

Weight 1,03 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour GREY
Cover Glass
Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 21.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska