


DOWNLIGHT SHERIFF M 930 31W 60° GREY PREMIUM WHITE ON/OFF

Article number: N204-K0001-HE930-HA-H60-ZC03_800-S6-###





_ED COB

Light colour 3000 [K] PREMIUM WHITE

CRI

90

 Led chip flux
 3911 [lm]

 Luminous flux
 3128 [lm]

 System power
 31 [W]

 Luminaire Efficiency
 101 [lm/W]

 Beam angle
 101 [lm/W]

Controller

MacAdam

60°

ON/OFF

3 SDCM

LUMINAIRE

Weight 1,03 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour GREY
Cover Glass
Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

Note: All data are typical values. Tolerance of measurements $\pm 10\%$ System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 15.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska