

DOWNLIGHT

DOWNLIGHT SHERIFF M 935 21W 60° GREY PREMIUM WHITE ON/OFF

Article number: N204-K0001-HE935-HA-H60-ZC02_550-S6-###



COB

90

3245 [lm]

2596 [lm]

124 [lm/W]

ON/OFF

3 SDCM

21 [W]

60°



000	Downi
3500 [K] PREMIUM WHITE	LED do
	on enq

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

LUMINAIRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	1,03 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 22.05.2024