


DOWNLIGHT SHERIFF M 930 11W 30° GREY PREMIUM COLOR ON/OFF

Article number: N204-K0001-PC930-HA-H30-ZC01_250-S6-###







COB 3000 [K] PREMIUM COLOR Light colour

CRI

90 Led chip flux 1145 [lm] Luminous flux 916 [lm] System power 11 [W] Luminaire Efficiency 83 [lm/W] Beam angle 30° Controller

ON/OFF MacAdam 3 SDCM

LUMINAIRE

Weight 1,03 [kg] Protection rating IP, IK, class IP 20, IK 3, GREY Luminaire colour Cover Glass Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska