


DOWNLIGHT SHERIFF M 940 20W 15° GREY PREMIUM WHITE ON/OFF

Article number: N204-K0001-PW940-HA-H15-ZC01_500-S6-###



3 SDCM





LED COB

Light colour 4000 [K] PREMIUM WHITE

CRI

90 Led chip flux

2663 [lm]

Luminous flux

System power

Luminaire Efficiency

20 [W]

107 [lm/W]

Controller

MacAdam

15°

ON/OFF

LUMINAIRE

Beam angle

Weight 1,03 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour GREY
Cover Glass
Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 22.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska