


## DOWNLIGHT SHERIFF M 840 25W 60° GREY | ON/OFF

Article number: N204-K0001-RF840-H8-H60-ZC02\_650-S6-###







| LED                  | COB        |
|----------------------|------------|
| Light colour         | 4000 [K]   |
| CRI                  | 80         |
| Led chip flux        | 3690 [lm]  |
| Luminous flux        | 2952 [lm]  |
| System power         | 25 [W]     |
| Luminaire Efficiency | 118 [Im/W] |
| Beam angle           | 60°        |
| Controller           | ON/OFF     |
| MacAdam              | 3 SDCM     |
|                      |            |

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

## LUMINAIRE

Weight 1,03 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour GREY

Cover Glass

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 21.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska