

DOWNLIGHT

DOWNLIGHT SHERIFF M 850 37W 30° GREY | ON/OFF

Article number: N204-K0001-RF850-H8-H30-ZC03_950-S6-###



LED	COB
Light colour	5000 [K]
CRI	80
Led chip flux	5502 [lm]
Luminous flux	4401 [lm]
System power	37 [W]
Luminaire Efficiency	119 [lm/W]
Beam angle	30°
Controller	ON/OFF
MacAdam	3 SDCM
UMINAIRE	
Weight	1,03 [kg]
Protection rating IP , IK , class	IP 20, IK 3,

GREY

Glass

220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

L

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 15.05.2024