

## DOWNLIGHT

# DOWNLIGHT SHERIFF M 940 23W 30° GREY | ON/OFF

Article number: N204-K0001-RF940-H8-H30-ZC02\_600-S6-###



COB

90

4000 [K] |

2899 [lm]

2319 [lm]

101 [lm/W]

ON/OFF

3 SDCM

23 [W]

30°



### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL patette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

# LUMINAIRE

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	1,03 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

# Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

#### **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



+48 32 388 80 00



Street: Ignatza Hakuby 18 41-914 Bytom, Polska