

## DOWNLIGHT SHERIFF M 940 21W 45° GREY | ON/OFF

Article number: N204-K0001-RF940-H8-H45-ZC02\_550-S6-###



Ø140mm

Ø155 mm

|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | 4000 [K]   |
| CRI                  | 90         |
| Led chip flux        | 2658 [lm]  |
| Luminous flux        | 2126 [lm]  |
| System power         | 21 [W]     |
| Luminaire Efficiency | 101 [lm/W] |
| Beam angle           | 45°        |
| Controller           | ON/OFF     |
| MacAdam              | 3 SDCM     |

### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

### LUMINAIRE

|                                   |                  |
|-----------------------------------|------------------|
| Weight                            | 1,03 [kg]        |
| Protection rating IP , IK , class | IP 20, IK 3,     |
| Luminaire colour                  | GREY             |
| Cover                             | Glass            |
| Operating voltage                 | 220-240V 50-60Hz |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 21.05.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska