

#### DOWNLIGHT

## DOWNLIGHT SHERIFF M 825 25W 30° GREY BREAD ON/OFF

Article number: N204-K0001-VF825-H8-H30-ZC02\_650-S6-###



СОВ

80

3042 [lm]

2433 [lm]

25 [W] 97 [lm/W]

30°

ON/OFF

3 SDCM

2500 [K] BREAD



#### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

### LUMINAIRE

Controller

MacAdam

Light colour

Led chip flux Luminous flux

System power

Luminaire Efficiency Beam angle

CRI

UNIVAILE .	
Weight	1,03 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

# Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.05.2024