


DOWNLIGHT SHERIFF M 930 27W 15° BLACK HI EFFICIENT ON/OFF

Article number: N204-K0002-BB930-H8-H15-ZC02_700-S6-###







LED	COB
Light colour	3000 [K] HI EFFICIENT
CRI	
Led chip flux	90
Lod only nax	4378 [lm]
Luminous flux	
System power	3502 [lm]
Gystem power	27 [W]
Luminaire Efficiency	
Beam angle	130 [lm/W]
beam angle	15°
Controller	
MacAdam	ON/OFF
Wathuaiii	3 SDCM

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LUMINAIRE

Weight 1,03 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 21.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska