


## DOWNLIGHT SHERIFF M 930 10W 30° BLACK HI EFFICIENT ON/OFF

Article number: N204-K0002-BB930-H8-H30-ZC01\_250-S6-###





COB 3000 [K] HI EFFICIENT Light colour CRI 90 Led chip flux 1623 [lm] Luminous flux 1298 [lm] System power 10 [W] Luminaire Efficiency 130 [lm/W] Beam angle 30° Controller ON/OFF MacAdam 3 SDCM

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

## LUMINAIRE

Weight 1,03 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour BLACK
Cover Glass
Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 15.05.2024



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska