


DOWNLIGHT SHERIFF M 940 27W 15° BLACK HI EFFICIENT ON/OFF

Article number: N204-K0002-BB940-H8-H15-ZC02_700-S6-###







| LED | | COB |
|----------------------|-----------|--------------------------|
| Light colour | | 4000 [K] HI EFFICIENT |
| CRI | | 90 |
| Led chip flux | | |
| Luminous flux | 4385 [lm] | |
| | | 3508 [lm] |
| System power | | 07.040 |
| Luminaire Efficiency | | 27 [W] |
| • | | 130 [lm/W] |
| Beam angle | | 4.50 |
| Controller | | 15° |
| MacAdam | | ON/OFF |
| | | 3 SDCM |
| | | 3 SDCIVI |

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

LUMINAIRE

Weight 1,03 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 22.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska