


## DOWNLIGHT SHERIFF M 940 31W 60° BLACK HI EFFICIENT ON/OFF

Article number: N204-K0002-BB940-H8-H60-ZC03\_800-S6-###







LED	COB
Light colour	4000 [K] HI EFFICIENT
CRI	
Led chip flux	90
Lea Chip hax	4964 [lm]
Luminous flux	.00.[]
Custom nauce	3971 [lm]
System power	31 [W]
Luminaire Efficiency	0.[44]
B	128 [lm/W]
Beam angle	60°
Controller	00
	ON/OFF
MacAdam	0.00014
	3 SDCM

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

## LUMINAIRE

 Weight
 1,03 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 BLACK

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 21.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska