


DOWNLIGHT SHERIFF M 957 31W 15° BLACK SPECIAL ON/OFF

Article number: N204-K0002-CC957-H8-H15-ZC03_800-S6-###



ON/OFF

3 SDCM





 LED
 COB

 Light colour
 5700 [K] SPECIAL

 CRI
 90

 Led chip flux
 3934 [Im]

 Luminous flux
 3147 [Im]

 System power
 31 [W]

 Luminaire Efficiency
 102 [Im/W]

 Beam angle
 15°

LUMINAIRE

Controller

MacAdam

 Weight
 1,03 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 BLACK

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 27M.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 21.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska