


## DOWNLIGHT SHERIFF M 957 10W 60° BLACK SPECIAL ON/OFF

Article number: N204-K0002-CC957-H8-H60-ZC01\_250-S6-###





COB

5700 [K] SPECIAL Light colour

CRI

Led chip flux 1318 [lm] Luminous flux 1054 [lm] System power 10 [W] Luminaire Efficiency 105 [lm/W] Beam angle 60° Controller ON/OFF

MacAdam 3 SDCM

## **LUMINAIRE**

Weight 1,03 [kg] Protection rating IP , IK , class IP 20, IK 3, BLACK Luminaire colour Cover Glass Operating voltage 220-240V 50-60Hz

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska