


DOWNLIGHT SHERIFF M 957 19W 60° BLACK SPECIAL ON/OFF

Article number: N204-K0002-CC957-H8-H60-ZC01_500-S6-###







LED COB
Light colour 5700 [K] SPECIAL

CRI 9

Led chip flux 2551 [lm]

Luminous flux 2040 [lm]

System power 19 [W]

Luminaire Efficiency 107 [lm/W]

Beam angle 60°

Controller ON/OFF

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

Weight 1,03 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 21.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska