

#### DOWNLIGHT

## DOWNLIGHT SHERIFF M 930 23W 15° BLACK CRI97 ON/OFF

Article number: N204-K0002-HI930-H8-H15-ZC02\_600-S6-###



COB

90

2601 [lm]

2080 [lm]

90 [lm/W]

ON/OFF

3 SDCM

23 [W]

15°

3000 [K] CRI97



#### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

### LUMINAIRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

1,03 [kg]
IP 20, IK 3,
BLACK
Glass
220-240V 50-60Hz
E

# Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



+48 32

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 22.05.2024