


DOWNLIGHT SHERIFF M 940 27W 45° BLACK PREMIUM WHITE ON/OFF

Article number: N204-K0002-PW940-HA-H45-ZC02_700-S6-###







LED COB

Light colour 4000 [K] PREMIUM WHITE

CRI

90

 Led chip flux
 3634 [lm]

 Luminous flux
 2907 [lm]

 System power
 27 [W]

 Luminaire Efficiency
 108 [lm/W]

 Beam angle
 108 [lm/W]

Controller

MacAdam

45°

ON/OFF

3 SDCM

LUMINAIRE

Weight 1,03 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour BLACK
Cover Glass
Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.

+48 32 388 80 00



Generated: 21.05.2024



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska