


DOWNLIGHT SHERIFF M 840 37W 60° BLACK | ON/OFF

Article number: N204-K0002-RF840-H8-H60-ZC03_950-S6-###







| LED | COB |
|----------------------|------------|
| Light colour | 4000 [K] |
| CRI | 80 |
| Led chip flux | 5394 [lm] |
| Luminous flux | 4315 [lm] |
| System power | 37 [W] |
| Luminaire Efficiency | 117 [lm/W] |
| Beam angle | 60° |
| Controller | ON/OFF |
| MacAdam | 3 SDCM |

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LUMINAIRE

Weight 1,03 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour BLACK

Cover Glass

Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 21.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska