

DOWNLIGHT

DOWNLIGHT SHERIFF M 850 23W 15° BLACK | ON/OFF

Article number: N204-K0002-RF850-H8-H15-ZC02_600-S6-###



LED	COB
Light colour	5000 [K]
CRI	80
Led chip flux	3475 [lm]
Luminous flux	2780 [lm]
System power	23 [W]
Luminaire Efficiency	121 [lm/W]
Beam angle	15°
Controller	ON/OFF
MacAdam	3 SDCM
LUMINAIRE	
Weight	1,03 [kg]

IP 20, IK 3,

220-240V 50-60Hz

BLACK

Glass

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Protection rating IP , IK , class

Luminaire colour

Operating voltage

+48 3

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 15.05.2024