

DOWNLIGHT

DOWNLIGHT SHERIFF M 850 27W 60° BLACK | ON/OFF

Article number: N204-K0002-RF850-H8-H60-ZC02_700-S6-###



COB

80

5000 [K] |

4053 [lm]

3242 [lm]

120 [lm/W]

ON/OFF

3 SDCM

27 [W]

60°



Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL patette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

LUMINAIRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	1,03 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00



cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska