


# DOWNLIGHT SHERIFF M 940 27W 15° BLACK | ON/OFF

Article number: N204-K0002-RF940-H8-H15-ZC02\_700-S6-###



|                      |            |
|----------------------|------------|
| LED                  | COB        |
| Light colour         | 4000 [K]   |
| CRI                  | 90         |
| Led chip flux        | 3383 [lm]  |
| Luminous flux        | 2706 [lm]  |
| System power         | 27 [W]     |
| Luminaire Efficiency | 100 [lm/W] |
| Beam angle           | 15°        |
| Controller           | ON/OFF     |
| MacAdam              | 3 SDCM     |

## Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

## LUMINAIRE

|                                   |                  |
|-----------------------------------|------------------|
| Weight                            | 1.03 [kg]        |
| Protection rating IP , IK , class | IP 20, IK 3,     |
| Luminaire colour                  | BLACK            |
| Cover                             | Glass            |
| Operating voltage                 | 220-240V 50-60Hz |

Note: All data are typical values. Tolerance of measurements +/-10%  
System features may change with product improvements due to technical advances.

## OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 27.09.2024



+48 32 388 80 00



www.cora.pl

cora@cora.pl



Street: Ignatza Hakuby 18

41-914 Bytom, Polska