


DOWNLIGHT SHERIFF M 825 31W 15° BLACK BREAD ON/OFF

Article number: N204-K0002-VF825-H8-H15-ZC03_800-S6-###



93 [lm/W]

3 SDCM



COB

2500 [K] BREAD Light colour

CRI

Led chip flux 3621 [lm] Luminous flux 2896 [lm] System power 31 [W] Luminaire Efficiency

Beam angle 15° Controller ON/OFF

LUMINAIRE

MacAdam

Weight 1,03 [kg] Protection rating IP , IK , class IP 20, IK 3, BLACK Luminaire colour Cover Glass Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska