

DOWNLIGHT SHERIFF M 930 21W 15° WHITE HI EFFICIENT ON/OFF

Article number: N204-K0003-BB930-H8-H15-ZC02_550-S6-###



Ø140mm

Ø155 mm

| | |
|----------------------|-----------------------|
| LED | COB |
| Light colour | 3000 [K] HI EFFICIENT |
| CRI | 90 |
| Led chip flux | 3487 [lm] |
| Luminous flux | 2789 [lm] |
| System power | 21 [W] |
| Luminaire Efficiency | 133 [lm/W] |
| Beam angle | 15° |
| Controller | ON/OFF |
| MacAdam | 3 SDCM |

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

LUMINAIRE

| | |
|-----------------------------------|------------------|
| Weight | 1,03 [kg] |
| Protection rating IP , IK , class | IP 20, IK 3, |
| Luminaire colour | WHITE |
| Cover | Glass |
| Operating voltage | 220-240V 50-60Hz |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 21.05.2024



+48 32 388 80 00



www.cora.pl
cora@cora.pl



Street: Ignatza Hakuby 18
41-914 Bytom, Polska