


## DOWNLIGHT SHERIFF M 930 34W 15° WHITE HI EFFICIENT ON/OFF

Article number: N204-K0003-BB930-H8-H15-ZC03\_900-S6-###



|                      |                       |
|----------------------|-----------------------|
| LED                  | COB                   |
| Light colour         | 3000 [K] HI EFFICIENT |
| CRI                  | 90                    |
| Led chip flux        | 5523 [lm]             |
| Luminous flux        | 4418 [lm]             |
| System power         | 34 [W]                |
| Luminaire Efficiency | 130 [lm/W]            |
| Beam angle           | 15°                   |
| Controller           | ON/OFF                |
| MacAdam              | 3 SDCM                |

### Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

### LUMINAIRE

|                                   |                  |
|-----------------------------------|------------------|
| Weight                            | 1,03 [kg]        |
| Protection rating IP , IK , class | IP 20, IK 3,     |
| Luminaire colour                  | WHITE            |
| Cover                             | Glass            |
| Operating voltage                 | 220-240V 50-60Hz |

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 21.05.2024



+48 32 388 80 00



www.cora.pl  
cora@cora.pl



Street: Ignatza Hakuby 18  
41-914 Bytom, Polska