

DOWNLIGHT

DOWNLIGHT SHERIFF M 935 36W 15° WHITE HI EFFICIENT ON/OFF

Article number: N204-K0003-BB935-H8-H15-ZC03_950-S6-###



LED	COB
Light colour	3500 [K] HI EFFICIENT
CRI Led chip flux Luminous flux System power Luminaire Efficiency Beam angle Controller MacAdam	90
	5518 [lm]
	50 at
	4414 [lm]
	36 [W]
	123 [lm/W]
	15°
	ON/OFF
May wan	3 SDCM
LUMINAIRE	
Weight	1,03 [kg]
Protection rating IP , IK , class	IP 20, IK 3,

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

Cover

Luminaire colour

Operating voltage

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.

WHITE

Glass

220-240V 50-60Hz





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 15.05.2024