


DOWNLIGHT SHERIFF M 935 36W 45° WHITE HI EFFICIENT ON/OFF

Article number: N204-K0003-BB935-H8-H45-ZC03_950-S6-###







LED	COB
Light colour	3500 [K] HI EFFICIENT
CRI	LITIOILINI
Led chip flux	90
	5518 [lm]
Luminous flux	4414 [lm]
System power	++++ [1111]
Luminaira Efficiency	36 [W]
Luminaire Efficiency	123 [lm/W]
Beam angle	
Controller	45°
	ON/OFF
MacAdam	0.00014
	3 SDCM

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

LUMINAIRE

Weight 1,03 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour WHITE
Cover Glass
Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 21.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska