


## DOWNLIGHT SHERIFF M 935 31W 60° WHITE HI EFFICIENT ON/OFF

Article number: N204-K0003-BB935-H8-H60-ZC03\_800-S6-###







LED	COB
Light colour	3500 [K] HI EFFICIENT
CRI	
Led chip flux	90
Lea Chip hax	4723 [lm]
Luminous flux	4720 [IIII]
	3778 [lm]
System power	0.4.514.5
Luminaire Efficiency	31 [W]
Luminaire Emolericy	122 [lm/W]
Beam angle	[, **]
-	60°
Controller	
MacAdam	ON/OFF
Iviaonuaiii	3 SDCM

## **Downlight LED**

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

## LUMINAIRE

Weight 1,03 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour WHITE
Cover Glass
Operating voltage 220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 22.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska