

# DOWNLIGHT

# DOWNLIGHT SHERIFF M 940 36W 15° WHITE HI EFFICIENT ON/OFF

Article number: N204-K0003-BB940-H8-H15-ZC03\_950-S6-###



COB

90

4000 [K] HI EFFICIENT

5811 [lm]

4648 [lm]

129 [lm/W]

ON/OFF

3 SDCM

36 [W]

15°



## Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

#### LUMINAIRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

| Weight                            | 1,03 [kg]        |
|-----------------------------------|------------------|
| Protection rating IP , IK , class | IP 20, IK 3,     |
| Luminaire colour                  | WHITE            |
| Cover                             | Glass            |
| Operating voltage                 | 220-240V 50-60Hz |

# Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

### **OPTIONS**

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 21.05.2024