


DOWNLIGHT SHERIFF M 957 27W 30° WHITE SPECIAL ON/OFF

Article number: N204-K0003-CC957-H8-H30-ZC02_700-S6-###



COB





 Light colour
 5700 [K] SPECIAL

 CRI
 90

 Led chip flux
 3484 [lm]

 Led chip flux
 3484 [lm]

 Luminous flux
 2787 [lm]

 System power
 27 [W]

 Luminaire Efficiency
 103 [lm/W]

 Beam angle
 30°

 Controller
 ON/OFF

Controller ON/OFF
MacAdam 3 SDCM

LUMINAIRE

Weight 1,03 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour WHITE

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 21.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska