


DOWNLIGHT SHERIFF M 930 11W 15° WHITE PREMIUM WHITE ON/OFF

Article number: N204-K0003-HE930-HA-H15-ZC01_250-S6-###







LED COB

Light colour 3000 [K] PREMIUM WHITE

CRI

90 Led chip flux

Luminous flux

System power

Luminaire Efficiency

1497 [lm]

1197 [lm]

11 [W]

109 [lm/W]

Beam angle 15°
Controller

MacAdam ON/OFF

LUMINAIRE

 Weight
 1,03 [kg]

 Protection rating IP , IK , class
 IP 20, IK 3,

 Luminaire colour
 WHITE

 Cover
 Glass

 Operating voltage
 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 21.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska