


DOWNLIGHT SHERIFF M 930 25W 45° WHITE PREMIUM WHITE ON/OFF

Article number: N204-K0003-HE930-HA-H45-ZC02_650-S6-###



3 SDCM





LED COB

Light colour 3000 [K] PREMIUM WHITE

CRI

90 Led chip flux

3659 [lm]

Luminous flux

System power

2927 [lm]

25 [W] Luminaire Efficiency

Beam angle

45° Controller

ON/OFF MacAdam

LUMINAIRE

Weight 1,03 [kg]
Protection rating IP , IK , class IP 20, IK 3,
Luminaire colour WHITE
Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 21.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska