


DOWNLIGHT SHERIFF M 940 31W 15° WHITE PREMIUM WHITE ON/OFF

Article number: N204-K0003-PW940-HA-H15-ZC03_800-S6-###







LED COB

Light colour 4000 [K] PREMIUM WHITE

CRI

Led chip flux

Luminous flux

90

4097 [Im]

System power 3277 [lm]
Luminaire Efficiency 31 [W]

106 [lm/W] Beam angle

15° Controller

ON/OFF MacAdam 3 SDCM

LUMINAIRE

Weight 1,03 [kg]

Protection rating IP , IK , class IP 20, IK 3,

Luminaire colour WHITE

Cover Glass

Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 22.05.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska