

DOWNLIGHT

DOWNLIGHT SHERIFF M 827 13W 45° WHITE | ON/OFF

Article number: N204-K0003-RF827-H8-H45-ZC01_350-S6-###



COB

80

2700 [K] |

1886 [lm]

1508 [lm]

116 [lm/W]

ON/OFF

3 SDCM

13 [W]

45°



Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

LUMINAIRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

1,03 [kg]
IP 20, IK 3,
WHITE
Glass
220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 22.05.2024