

DOWNLIGHT

DOWNLIGHT SHERIFF M 940 14W 15° WHITE | ON/OFF

Article number: N204-K0003-RF940-H8-H15-ZC01_350-S6-###



COB

90

4000 [K] |

1691 [lm]

1352 [lm]

97 [lm/W]

ON/OFF

3 SDCM

14 [W]

15°



Downlight LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beams available: 15°, 30°, 45° and 60°. Maximum power is 37W.

LUMINAIRE

Light colour

Led chip flux

Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	1,03 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features

may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00



 \bigcirc

Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 22.05.2024