

DOWNLIGHT

DOWNLIGHT SHERIFF Z 930 21W 55° GREY | ON/OFF

COB

90 2536 [lm]

3000 [K] |

2028 [lm]

97 [lm/W]

ON/OFF

3 SDCM

21 [W]

36°

Article number: N206-K0001-RF930-H8-###-ZC02_550-##-###



D			-
Down	iign	τLE	Ð

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

 м	ΝΛ	IRE

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	1,23 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	GREY
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



+48

+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024