

DOWNLIGHT

## DOWNLIGHT SHERIFF Z 840 19W 55° BLACK | ON/OFF

СОВ

80 2839 [lm]

4000 [K] |

2271 [lm]

120 [lm/W]

ON/OFF

3 SDCM

19 [W]

36°

Article number: N206-K0002-RF840-H8-###-ZC01\_500-##-###



Downli	abt	
DOWIII	ynu	LED

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

LL	JM	INA	IR	Е

Light colour

Led chip flux Luminous flux

System power

Beam angle

Controller

MacAdam

Luminaire Efficiency

CRI

Weight	1,23 [kg]
weight	1,20 [KY]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

## OPTIONS

RAL colours on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024