

DOWNLIGHT

DOWNLIGHT SHERIFF Z 930 25W 55° WHITE CRI97 ON/OFF

СОВ

90 2797 [lm]

2237 [lm]

25 [W] 89 [lm/W]

36°

ON/OFF

3 SDCM

3000 [K] CRI97

Article number: N206-K0003-HI930-H8-###-ZC02_650-##-###





Down	lia	ht	I FD
DOWN	''y		

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

LU	М	NA	IRE

Controller

MacAdam

Light colour

Led chip flux Luminous flux

System power

Luminaire Efficiency Beam angle

CRI

Weight	1,23 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	WHITE
Cover	Glass
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 26.06.2024