

DOWNLIGHT SHERIFF Z BATWING 850 27W 90°x50° BLACK | ON/OFF

COB

80

5000 [K] |

4053 [lm]

3242 [lm]

27 [W] 120 [lm/W]

90°x50°

ON/OFF

3 SDCM

Article number: N207-K0002-RF850-H8-ZBW-ZC02_700-B1-###



(cutout) Ø210mm

D			-
Down	iign	τLE	Ð

LED downlight for drop ceiling installation. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Special double asymmetric optics. Maximum power is 37W.

LU	MI	NA	IR	E

Controller

MacAdam

Light colour

Led chip flux

Luminous flux

System power

Luminaire Efficiency Beam angle

CRI

M/ 1 1	
Weight	1,23 [kg]
Protection rating IP , IK , class	IP 20, IK 3,
Luminaire colour	BLACK
Cover	Plastic
Operating voltage	220-240V 50-60Hz

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.





+48 32 388 80 00

www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska Generated: 29.06.2024