


DOWNLIGHT SHERIFF I 930 35W 55° GREY PREMIUM WHITE ON/OFF

Article number: N208-K0001-HE930-HA-###-ZC03_900-##-###







LED COB

Light colour 3000 [K] PREMIUM WHITE

CRI

90

 Led chip flux
 3911 [lm]

 Luminous flux
 3128 [lm]

 System power
 35 [W]

 Luminaire Efficiency
 89 [lm/W]

 Beam angle
 36°

 Controller
 36°

Controller

MacAdam

3 SDCM

LUMINAIRE

Weight 1 [kg]
Protection rating IP , IK , class IP 65, IK 3,
Luminaire colour GREY
Cover Glass
Operating voltage 220-240V 50-60Hz

Downlight LED

LED downlight for drop ceiling installation. IP65 rated. Aluminium housing. Glass cover included. Available in white, black and grey. Any RAL palette colour available on enquiry. Reflector beam available: 55°. Maximum power is 37W.

Note: All data are typical values. Tolerance of measurements +/-10% System features may change with product improvements due to technical advances.

OPTIONS

RAL colours on enquiry, honeycomb louver on enquiry , Casambi on enquiry, DALI on enquiry, Phase-cut dimming on enquiry.



Generated: 26.06.2024



+48 32 388 80 00



www.cora.pl cora@cora.pl



Street: Ignatza Hakuby 18 41-914 Bytom, Polska